SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 260783 - Burgundy Mist metallic NitorLACK G

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Coatings for wood. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Valresa Coatings, S.A.
Pol. Ind. Reva S-13 Avda. dels Gremis s/n
46190 Riba-roja de Turia - Valencia - Spain
Phone.: +34 961669560 - Fax: +34 961668665
safety@valresa.com
www.valresa.com

1.4 Emergency telephone number: +34 961669560 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318
Flam. Liq. 2: Flammable liquids, Category 2, H225
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger

Hazard statements:

Causes serious eye damage
Highly flammable liquid and vapour
May cause an allergic skin reaction
May cause drowsiness or dizziness

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Wear protective gloves/protective clothing/eye protection/face protection
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
In case of fire: Use ABC powder extinguisher to extinguish
Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

Repeated exposure may cause skin dryness or cracking

Substances that contribute to the classification

N-butyl acetate; 2-methoxy-1-methylethyl acetate; Ethyl acetate; Rosin, maleated

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

3.2 Mixture:

Chemical description: Mixture composed of additives, colourants, resins and nitrocelluloses in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification			Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	**N-butyl acetate**□[1]□		ATP CLP00	**10 - <25 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning		
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	**2-methoxy-1-methylethyl acetate**□[1]□		Self-classified	**10 - <25 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning		
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	**Ethyl acetate**□[1]□		ATP CLP00	**2,5 - <10 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger		
CAS: 8050-28-0 EC: 232-480-4 Index: Non-applicable REACH: 01-2119527624-39-XXXX	**Rosin, maleated**□[1]□		Self-classified	**2,5 - <10 %**
	Regulation 1272/2008	Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger		
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	**Xylene**□[1]□		ATP CLP00	**2,5 - <10 %**
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning		
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	**Propan-2-ol**□[1]□		ATP CLP00	**2,5 - <10 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger		
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	**1-methoxy-2-propanol**□[1]□		ATP ATP01	**2,5 - <10 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning		
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	**Ethylbenzene**□[1]□		ATP ATP06	**1 - <2,5 %**
	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger		
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	**2-butoxyethanol**□[2]□		ATP CLP00	**0,25 - <1 %**
	Regulation 1272/2008	Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning		
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	**2-butanone**□[2]□		ATP CLP00	**0,25 - <1 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger		

□[1]□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830
□[2]□ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

*** Changes with regards to the previous version*

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -

SECTION 4: FIRST AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO☐). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

- CONTINUED ON NEXT PAGE -

SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,…) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 ºC

Maximum Temp.: 35 ºC

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m³
CAS: 108-65-6	IOELV (STEL)	100 ppm	550 mg/m³
EC: 203-603-9	Year	2017	
Ethyl acetate	IOELV (8h)	200 ppm	734 mg/m³
CAS: 141-78-6	IOELV (STEL)	400 ppm	1468 mg/m³
EC: 205-500-4	Year	2018	
Xylene	IOELV (8h)	50 ppm	221 mg/m³
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m³
EC: 215-535-7	Year	2018	
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m³
CAS: 107-98-2	IOELV (STEL)	150 ppm	563 mg/m³
EC: 203-539-1	Year	2018	
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m³
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m³
EC: 202-849-4	Year	2018	
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m³
CAS: 111-76-2	IOELV (STEL)	50 ppm	246 mg/m³
EC: 203-905-0	Year	2018	
2-butanone	IOELV (8h)	200 ppm	600 mg/m³
CAS: 78-93-3	IOELV (STEL)	300 ppm	900 mg/m³
EC: 201-159-0	Year	2018	

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	960 mg/m³	960 mg/m³	480 mg/m³	480 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	275 mg/m³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m³	1468 mg/m³	734 mg/m³	734 mg/m³
Rosin, maleated	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 8050-28-0	Dermal	Non-applicable	Non-applicable	3 mg/kg	Non-applicable
EC: 232-480-4	Inhalation	Non-applicable	Non-applicable	19 mg/m³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	289 mg/m³	289 mg/m³	77 mg/m³	Non-applicable
Propan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	500 mg/m³	Non-applicable
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	50,6 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	553,5 mg/m³	369 mg/m³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m³	77 mg/m³	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	663 mg/m³	246 mg/m³	98 mg/m³	Non-applicable
2-butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	859,7 mg/m³	859,7 mg/m³	102,34 mg/m³	102,34 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m³	734 mg/m³	367 mg/m³	367 mg/m³
Rosin, maleated	Oral	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
CAS: 8050-28-0	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
EC: 232-480-4	Inhalation	Non-applicable	Non-applicable	6 mg/m³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m³	Non-applicable
Propan-2-ol	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	89 mg/m³	Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	3,3 mg/kg	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	18,1 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m³	Non-applicable
2-butoxyethanol	Oral	13,4 mg/kg	Non-applicable	3,2 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	44,5 mg/kg	Non-applicable	38 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m³	123 mg/m³	49 mg/m³	Non-applicable
2-butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable

PNEC:

Identification				
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	200 g/kg	Sediment (Marine water)	0,115 mg/kg
Rosin, maleated	STP	1,25 mg/L	Fresh water	0,0048 mg/L
CAS: 8050-28-0	Soil	0,001 mg/kg	Marine water	0,00048 mg/L
EC: 232-480-4	Intermittent	0,048 mg/L	Sediment (Fresh water)	0,019 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,002 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	160 g/kg	Sediment (Marine water)	552 mg/kg
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	10 mg/L
CAS: 107-98-2	Soil	5,49 mg/kg	Marine water	1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	3,13 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	9,1 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2-butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1000 g/kg	Sediment (Marine water)	284,7 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.
All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CE CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CE CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CE CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer´s instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	62,17 % weight
V.O.C. density at 25 ºC:	613 kg/m³ (613 g/L)
Average carbon number:	5,68
Average molecular weight:	108,01 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:	
Physical state at 20 ºC:	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	114 ºC
Vapour pressure at 25 ºC:	4089 Pa
Vapour pressure at 50 ºC:	13428 Pa (13 kPa)
Evaporation rate at 25 ºC:	Non-applicable *
Product description:	
Density at 25 ºC:	986 kg/m³
Relative density at 25 ºC:	0,986
Dynamic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 40 ºC:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 ºC:	Non-applicable *
Partition coefficient n-octanol/water 25 ºC:	Non-applicable *
Solubility in water at 25 ºC:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	20 ºC
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	238 ºC
Lower flammability limit:	Not available

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Upper flammability limit:	Not available
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 25 ºC:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Propan-2-ol	LD50 oral	5280 mg/kg	Rat
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	>20 mg/L (4 h)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Rosin, maleated	LD50 oral	>2000 mg/kg	
CAS: 8050-28-0	LD50 dermal	>2000 mg/kg	
EC: 232-480-4	LC50 inhalation	>5 mg/L (4 h)	

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Genus
1-methoxy-2-propanol	LD50 oral	>2000 mg/kg	
CAS: 107-98-2	LD50 dermal	>2000 mg/kg	
EC: 203-539-1	LC50 inhalation	>20 mg/L (4 h)	
2-butoxyethanol	LD50 oral	1414 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	1060 mg/kg	Rabbit
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)	Rat
2-butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat

*** Changes with regards to the previous version*

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
N-butyl acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
2-butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Degradability		Biodegradability	
Ethyl acetate	BOD5	1.36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1.69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0.81	% Biodegradable	83 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
Propan-2-ol	BOD5	1.19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2.23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0.53	% Biodegradable	86 %
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %
2-butanone	BOD5	2.03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2.31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0.88	% Biodegradable	89 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Ethyl acetate	BCF	30
CAS: 141-78-6	Pow Log	0.73
EC: 205-500-4	Potential	Moderate
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
Propan-2-ol	BCF	3
CAS: 67-63-0	Pow Log	0.05
EC: 200-661-7	Potential	Low
1-methoxy-2-propanol	BCF	3
CAS: 107-98-2	Pow Log	-0.44
EC: 203-539-1	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
2-butoxyethanol	BCF	3
CAS: 111-76-2	Pow Log	0.83
EC: 203-905-0	Potential	Low
2-butanone	BCF	3
CAS: 78-93-3	Pow Log	0.29
EC: 201-159-0	Potential	Low

12.4 Mobility in soil:

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Absorption/desorption		Volatility	
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 ºC)	Moist soil	Non-applicable
Ethyl acetate	Koc	59	Henry	13,58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 ºC)	Moist soil	Yes
Xylene	Koc	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Propan-2-ol	Koc	1.5	Henry	8,207E-1 Pa·m³/mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 ºC)	Moist soil	Yes
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 ºC)	Moist soil	Yes
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 ºC)	Moist soil	Yes
2-butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 ºC)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

*** Changes with regards to the previous version*

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

- CONTINUED ON NEXT PAGE -

SECTION 14: TRANSPORT INFORMATION (continued)

14.1	**UN number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Special regulations:	163, 367, 640D, 650
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	**Transport in bulk according to Annex II of Marpol and the IBC Code:**	Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

14.1	**UN number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Special regulations:	367, 163
	EmS Codes:	F-E, S-E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	**Transport in bulk according to Annex II of Marpol and the IBC Code:**	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2018:

14.1	**UN number:**	UN1263
14.2	**UN proper shipping name:**	PAINT
14.3	**Transport hazard class(es):**	3
	Labels:	3
14.4	**Packing group:**	II
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Physico-Chemical properties:	see section 9
14.7	**Transport in bulk according to Annex II of Marpol and the IBC Code:**	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
— metallic glitter intended mainly for decoration,
— artificial snow and frost,
— "whoopee" cushions,
— silly string aerosols,
— imitation excrement,
— horns for parties,
— decorative flakes and foams,
— artificial cobwebs,
— stink bombs.
Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
'For professional users only'.
Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Aluminium powder (stabilised). Product under the provisions of Article 9

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
  2-methoxy-1-methylethyl acetate (108-65-6)
- Removed substances
  2-methoxy-1-methylethyl acetate (108-65-6)

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness
H318: Causes serious eye damage
H317: May cause an allergic skin reaction
H225: Highly flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Acute Tox. 4: H332 - Harmful if inhaled
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method
Eye Dam. 1: Calculation method
Skin Sens. 1: Calculation method
Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu
http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol–water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -