250724 - NitorLACK SHELL PINK Spray

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 250724 - NitorLACK SHELL PINK Spray

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Spray paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Valresa Coatings, S.A.
Pol. Ind. Reva S-13 Avda. dels Gremis s/n
46190 Riba-roja de Turia Valencia - Spain
Phone: +34 961669560
www.valresa.com

1.4 Emergency telephone number: +34 961669560 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229
Aerosol 1: Flammable aerosols, Category 1, H222
Eye Irrit. 2: Eye irritation, Category 2, H319
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger

Hazard statements:

Pressurised container: May burst if heated.
Extremely flammable aerosol.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements:

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

Repeated exposure may cause skin dryness or cracking.

Substances that contribute to the classification

Butanone; acetone; N-butyl acetate; Ethyl acetate

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, aggregates, nitrocelluloses, pigments, plasticizers and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	**Dimethyl ether**(1) ATP CLP00		**25 - <50 %**
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	**Butanone**(2) ATP CLP00		**10 - <25 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	**acetone**(2) ATP CLP00		**10 - <25 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	**N-butyl acetate**(2) ATP CLP00		**2,5 - <5 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	**Ethyl acetate**(2) ATP CLP00		**1 - <2,5 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	**Xylene**(2) Self-classified		**1 - <2,5 %**
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 109-60-4 EC: 203-686-1 Index: 607-024-00-6 REACH: 01-2119484620-39-XXXX	**Propyl acetate**(2) ATP CLP00		**1 - <2,5 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	**2-methoxy-1-methylethyl acetate**(1) Self-classified		**0,25 - <1 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	**Ethylbenzene**(1) Self-classified		**0,25 - <1 %**
	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	
CAS: 108-94-1 EC: 203-631-1 Index: 606-010-00-7 REACH: 01-2119453616-35-XXXX	**Cyclohexanone**(1) Self-classified		**<0,25 %**
	Regulation 1272/2008	Acute Tox. 4: H302+H312+H332; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Danger	
CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40-XXXX	**Reaction mass of ethylbenzene and xylene**(1) Self-classified		**<0,25 %**
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	**Toluene**(1) ATP CLP00		**<0,25 %**
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	

(1) Substance with a Union workplace exposure limit
(2) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Chemical name/Classification		Concentration
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	**2-methoxy-1-methylethyl acetate**(1) ATP ATP01		**<0,25 %**
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	**Toluene**(1) Self-classified		**<0,25 %**
	Regulation 1272/2008	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	

(1) Substance with a Union workplace exposure limit
(2) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	% (w/w) >=10: STOT RE 2 - H373

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Xylene	LD50 oral	Non-applicable	
CAS: 1330-20-7	LD50 dermal	Non-applicable	
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	

*** Changes with regards to the previous version*

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

- CONTINUED ON NEXT PAGE -

SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO_2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

- CONTINUED ON NEXT PAGE -

SECTION 7: HANDLING AND STORAGE (continued)

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 ºC

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC,Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Dimethyl ether	IOELV (8h)	1000 ppm	1920 mg/m³
CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)		
acetone	IOELV (8h)	500 ppm	1210 mg/m³
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)		
Butanone	IOELV (8h)	200 ppm	600 mg/m³
CAS: 78-93-3 EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m³
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m³
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m³
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m³
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m³
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m³
Xylene	IOELV (8h)	50 ppm	221 mg/m³
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m³
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m³
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m³
Toluene	IOELV (8h)	50 ppm	192 mg/m³
CAS: 108-88-3 EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m³
Cyclohexanone	IOELV (8h)	10 ppm	40,8 mg/m³
CAS: 108-94-1 EC: 203-631-1	IOELV (STEL)	20 ppm	81,6 mg/m³
Ethyl acetate	IOELV (8h)	200 ppm	734 mg/m³
CAS: 141-78-6 EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m³
Toluene	IOELV (8h)	50 ppm	192 mg/m³
CAS: 108-88-3 EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m³
Reaction mass of ethylbenzene and xylene	IOELV (8h)	50 ppm	221 mg/m³
CAS: Non-applicable EC: 905-588-0	IOELV (STEL)	100 ppm	442 mg/m³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	1894 mg/m³	Non-applicable
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m³	Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m³	1210 mg/m³	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m³	600 mg/m³	300 mg/m³	300 mg/m³
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m³	1468 mg/m³	734 mg/m³	734 mg/m³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m³	442 mg/m³	221 mg/m³	221 mg/m³
Propyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 109-60-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 203-686-1	Inhalation	Non-applicable	840 mg/m³	Non-applicable	420 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m³	275 mg/m³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m³	77 mg/m³	Non-applicable
Cyclohexanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-94-1	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
EC: 203-631-1	Inhalation	80 mg/m³	80 mg/m³	40 mg/m³	40 mg/m³
Reaction mass of ethylbenzene and xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 905-588-0	Inhalation	442 mg/m³	442 mg/m³	221 mg/m³	221 mg/m³
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m³	384 mg/m³	192 mg/m³	192 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m³	275 mg/m³	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m³	384 mg/m³	192 mg/m³	192 mg/m³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	471 mg/m³	Non-applicable
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m³	Non-applicable
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m³	300 mg/m³	35,7 mg/m³	35,7 mg/m³

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m³	734 mg/m³	367 mg/m³	367 mg/m³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m³	260 mg/m³	65,3 mg/m³	65,3 mg/m³
Propyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 109-60-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 203-686-1	Inhalation	298 mg/m³	420 mg/m³	149 mg/m³	210 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m³	33 mg/m³
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m³	Non-applicable
Cyclohexanone	Oral	1,5 mg/kg	Non-applicable	1,5 mg/kg	Non-applicable
CAS: 108-94-1	Dermal	1 mg/kg	Non-applicable	1 mg/kg	Non-applicable
EC: 203-631-1	Inhalation	20 mg/m³	40 mg/m³	10 mg/m³	20 mg/m³
Reaction mass of ethylbenzene and xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 905-588-0	Inhalation	260 mg/m³	260 mg/m³	65,3 mg/m³	65,3 mg/m³
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m³	226 mg/m³	56,5 mg/m³	56,5 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m³	33 mg/m³
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m³	226 mg/m³	56,5 mg/m³	56,5 mg/m³

PNEC:

Identification				
Dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Propyl acetate	STP	1 mg/L	Fresh water	0,06 mg/L
CAS: 109-60-4	Soil	0,021 mg/kg	Marine water	0,006 mg/L
EC: 203-686-1	Intermittent	0,6 mg/L	Sediment (Fresh water)	0,16 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,016 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Cyclohexanone	STP	10 mg/L	Fresh water	0,033 mg/L
CAS: 108-94-1	Soil	0,03 mg/kg	Marine water	0,003 mg/L
EC: 203-631-1	Intermittent	0,329 mg/L	Sediment (Fresh water)	0,249 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,025 mg/kg
Reaction mass of ethylbenzene and xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: Non-applicable	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 905-588-0	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Eye and face protection

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Non-applicable

E.- Body protection

Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	88,75 % weight
V.O.C. density at 25 ºC:	Non-applicable
Average carbon number:	4,02
Average molecular weight:	74,04 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 ºC:	Aerosol
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	-25 ºC (Propellant)
Vapour pressure at 25 ºC:	Non-applicable *
Vapour pressure at 50 ºC:	<300000 Pa (300 kPa)
Evaporation rate at 25 ºC:	Non-applicable *
Product description:	
Density at 25 ºC:	Non-applicable *
Relative density at 25 ºC:	Non-applicable *
Dynamic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 25 ºC:	Non-applicable *
Kinematic viscosity at 40 ºC:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 ºC:	Non-applicable *
Partition coefficient n-octanol/water 25 ºC:	Non-applicable *
Solubility in water at 25 ºC:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability:

Flash Point:	Non-applicable
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	240 ºC (Propellant)
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 25 ºC:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

In case of prolonged thermal treatment at temperatures greater than 200 ºC, the decomposition products are aromatic amines (3,3´- dichlorobenzidine)

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  IARC: Reaction mass of ethylbenzene and xylene (3); Hydrocarbons, C9, aromatics (3); propan-2-ol (3); Xylene (3); Ethylbenzene (2B); Toluene (3); Solvent naptha (petroleum), light aromatic (3); Cyclohexanone (3); Toluene (3); Reaction mass of ethylbenzene and xylene (3); C.I.Pigment yellow 83 (1); Diiron trioxide (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether	LD50 oral	>2000 mg/kg	
CAS: 115-10-6	LD50 dermal	>2000 mg/kg	
EC: 204-065-8	LC50 inhalation	308,5 mg/L (4 h)	Rat

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Genus
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
Propyl acetate	LD50 oral	>2000 mg/kg	
CAS: 109-60-4	LD50 dermal	>2000 mg/kg	
EC: 203-686-1	LC50 inhalation	>20 mg/L	
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	>20 mg/L	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	>5000 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Cyclohexanone	LD50 oral	1890 mg/kg	Rat
CAS: 108-94-1	LD50 dermal	1100 mg/kg	Rabbit
EC: 203-631-1	LC50 inhalation	>20 mg/L	
Reaction mass of ethylbenzene and xylene	LD50 oral	2100 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	1100 mg/kg	Rat
EC: 905-588-0	LC50 inhalation	11 mg/L (4 h)	Rat
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

*** Changes with regards to the previous version*

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Cyclohexanone	LC50	527 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-94-1	EC50	800 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-631-1	EC50	370 mg/L (192 h)	Scenedesmus quadricauda	Algae
Toluene	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 108-88-3	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 203-625-9	EC50	Non-applicable		
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Concentration		Species	Genus
Reaction mass of ethylbenzene and xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: Non-applicable EC: 905-588-0	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Butanone	BOD5	2,03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Cyclohexanone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-94-1	COD	Non-applicable	Period	14 days
EC: 203-631-1	BOD5/COD	Non-applicable	% Biodegradable	87 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Butanone	BCF	3
CAS: 78-93-3	Pow Log	0.29
EC: 201-159-0	Potential	Low
acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Bioaccumulation potential	
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
Ethyl acetate	BCF	30
CAS: 141-78-6	Pow Log	0.73
EC: 205-500-4	Potential	Moderate
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
Cyclohexanone	BCF	2
CAS: 108-94-1	Pow Log	0.81
EC: 203-631-1	Potential	Low
Reaction mass of ethylbenzene and xylene	BCF	9
CAS: Non-applicable	Pow Log	2.77
EC: 905-588-0	Potential	Low
Toluene	BCF	90
CAS: 108-88-3	Pow Log	2.73
EC: 203-625-9	Potential	Moderate
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Toluene	BCF	90
CAS: 108-88-3	Pow Log	2.73
EC: 203-625-9	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether	Koc	Non-applicable	Henry	Non-applicable
CAS: 115-10-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-065-8	Surface tension	1,136E-2 N/m (25 ºC)	Moist soil	Non-applicable
Butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 ºC)	Moist soil	Yes
acetone	Koc	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 ºC)	Moist soil	Yes
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 ºC)	Moist soil	Non-applicable
Ethyl acetate	Koc	59	Henry	13,58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 ºC)	Moist soil	Yes
Xylene	Koc	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Absorption/desorption		Volatility	
Propyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 109-60-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-686-1	Surface tension	2,386E-2 N/m (25 ºC)	Moist soil	Non-applicable
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 ºC)	Moist soil	Yes
Cyclohexanone	Koc	17	Henry	9,119E-1 Pa·m³/mol
CAS: 108-94-1	Conclusion	Very High	Dry soil	Yes
EC: 203-631-1	Surface tension	3,437E-2 N/m (25 ºC)	Moist soil	Yes
Toluene	Koc	178	Henry	672,8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 ºC)	Moist soil	Yes
Toluene	Koc	178	Henry	672,8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 ºC)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

*** Changes with regards to the previous version*

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

SECTION 14: TRANSPORT INFORMATION (continued)

14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Special regulations:	190, 327, 344, 625
	Tunnel restriction code:	D
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Marine pollutant:**	No
14.6	**Special precautions for user**	
	Special regulations:	63, 959, 190, 277, 327, 344
	EmS Codes:	F-D, S-U
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
	Segregation group:	Non-applicable
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Physico-Chemical properties:	see section 9
14.7	**Maritime transport in bulk according to IMO instruments:**	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.
Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
  2-methoxy-1-methylethyl acetate (108-65-6)

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H229: Pressurised container: May burst if heated.
H222: Extremely flammable aerosol.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Gas 1A: H220 - Extremely flammable gas.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method
STOT SE 3: Calculation method
Aerosol 1: Calculation method
Aerosol 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu
http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -